

Memory Pressure Gauge 1.25" Quartz DXB

Features

- Super Seal Technology
– 30,000 psi at 1.25" OD
- 200°C Option
- Modular Memory Cartridge
- 2 Million Sample Capacity
- Inconel 718 or MP35N – NACE MR0175

1.25" OD Quartz Gauge - Inconel 718				
Pressure		Temperature		Part No.
690 bar	10,000 psi	150 °C	300 °F	2710.01.00711
1,100 bar	16,000 psi	150 °C	300 °F	2710.01.00228
1,100 bar	16,000 psi	177 °C	350 °F	2710.01.00229
1,350 bar	20,000 psi	177 °C	350 °F	2710.01.00230
1,350 bar	20,000 psi	200 °C	390 °F	2710.01.00231
1,700 bar	25,000 psi	177 °C	350 °F	2710.01.00232
1,700 bar	25,000 psi	200 °C	390 °F	2710.01.00233
2,000 bar	30,000 psi	200 °C	390 °F	2710.01.00234

Accessory Type	Part No.
Replaceable Memory Module 177°C	2710.01.00024
Replaceable Memory Module 200°C	2710.01.00765
Welded Bullnose Inconel 718	2710.01.00128
Welded Crossover 0.75-16 Inconel 718	2710.01.00129
Crossover 0.25 NPT Inconel 718	2710.01.00130
Battery Barrel 1 x "Sub CC" Inconel 718	2710.01.00713
Battery Barrel 2 x "Sub CC" Inconel 718	2710.01.01006
Replaceable SRO Module 150°C	2710.01.01864
SRO Housing Inconel 718	2710.01.01819
Pelican Case Assembly	2710.01.00235
USB To Serial Converter Assembly	2710.01.00682
Redress Kit Viton 90	2710.01.00908
Redress Kit Aflas	2710.01.00237
Redress Kit Chemraz	2710.01.00238

Specifications		
	Pressure	Temperature
Accuracy	0.02% F.S.	0.25 °C
Resolution	0.00006% F.S.	0.005 °C
Drift	< 3 psi / year	< 0.1 °C / year
Capacity	2 Million Samples	
Communication Method	USB	

