

## Accessories for Memory Pressure Gauge NEW Smart Battery Packs

The battery packs are now available with capacity measurement circuits.

These new “smart battery packs” record the current draw from each lithium battery cell and give users an accurate measurement of the battery packs remaining life.

The recorded battery capacity can be read by DataCan’s easy to use gauge software.

C - 4 Pin Lemo Connector					
Size	Max Temp	Volts	Ahr	Part No.	Product
C	125 °C	3.6	7.5	2710.01.02055	1.25" Piezo
	150 °C		6.2	2710.01.02056	
	165 °C		6.2	2710.01.02057	
	180 °C		5.0	2710.01.02058	
2 x C	125 °C		15.0	2710.01.02059	
	150 °C		12.4	2710.01.02060	
	165 °C		12.4	2710.01.02061	
	180 °C		10.0	2710.01.02062	

Sub CC - Threaded Locking 4 Pin Lemo Connector					
Size	Max Temp	Volts	Ahr	Part No.	Product
Sub CC	150 °C	3.6	10.0	2710.01.02063	1.25" Quartz
	165 °C		9.0	2710.01.02064	
	200 °C		6.2	2710.01.02065	
2 x Sub CC	150 °C		20.0	2710.01.02066	
	165 °C		18.0	2710.01.02067	
	200 °C		12.4	2710.01.02068	

C - Threaded Locking 4 Pin Lemo Connector					
Size	Max Temp	Volts	Ahr	Part No.	Product
C	125 °C	3.6	7.5	2710.01.02069	1.375" Welded Piezo
	165 °C		6.2	2710.01.02070	
	180 °C		5.0	2710.01.02071	
	200 °C		4.5	2710.01.02072	
2 x C	125 °C		15.0	2710.01.02073	
	165 °C		12.4	2710.01.02074	
	180 °C		10.0	2710.01.02075	
	200 °C		9.0	2710.01.02076	

